


DESCRIPTION:

The products are 4-pin optical relays. The device is a very small outline non-leaded photorelay suitable for surface-mount assembly. It consists of an infrared LED optically coupled to a photo-MOSFET and is housed in a SSON4 package. It features low output capacitance, COFF, and thus fast on/off switching of a high-frequency signal, making it ideal for switching applications in high-speed testers. The products are widely used in automatic test equipment, high-speed logic IC testers, high-speed memory testers and measuring instruments.



MAIN FEATURES

Isolation voltage 500 Vrms

Operating temperature range -40°C to 110°C

REACH & RoHS compliance

HBM: H3A; MM: M4; CDM: C3

CQC approved

VDE approved

UL approved

ABSOLUTE MAXIMUM RATINGS (Temperature=25°C)

Input	Forward Current	I_F	50	mA
	Peak Forward Current	I_{FP}	1	A
	Reverse Voltage	V_R	6	V
	Input Power Dissipation	P_D	75	mW
Detector	Off-state Output Terminal Voltage	V_{OFF}	20	V
	On-state Current	I_{ON}	2	A
	On-state Current (pulsed)	I_{ONP}	6	A
Isolation Voltage		V_{iso}	500	Vrms
Operating Temperature		T_{opr}	-40~110	
Junction Temperature		T_j	125	
Storage Temperature		T_{stg}	-55~125	



Soldering Temperature	T_{sol}	260	
-----------------------	-----------	-----	--

NOTE1

NOTE2

ELECTRICAL CHARACTERISTICS (Temperature=25°C)

Input	Forward Voltage	V_F	$I_F=10mA$	-	2	2.5	V
	Reverse Current	I_R	$V_R=6V$	-	-	1	μA
	Input Capacitance	C_{in}	$V=0V$ $f=1MHz$	-	30	-	pF
Detector	Off-state Current	I_{OFF}	$V_{OFF}=20V$	-	-	1	nA
	Output Capacitance	C_{OFF}	$V=0V$ $f=1MHz$ $t<1s$	-	120	-	pF
Coupled	Trigger LED Current	I_{FT}	$I_{ON}=2A$	-	-	1	mA
	Return LED Current	I_{FC}	$I_{OFF}=10\mu A$	0.1	-	-	mA
	On-state Resistance	R_{ON}	$I_{ON}=2A$ $I_F=5mA$ $t<1s$	-	0.1	0.2	Ω
Switching Characteristics	Isolation Resistance	R_{ISO}	DC500V 40~60%R.H.	-	10^{14}	-	Ω
	Turn On Time	t_{on}	$I_F=5mA$	-	0.1	1	ms
	Turn Off Time	t_{off}	$I_L=Max.$	-	0.2	1	ms

Recommended Operating Conditions

Supply Voltage	V_{DD}	-	-		V
Input Forward Current	I_F	5	7.5	20	mA
On-state Current	I_{ON}	-	-	2	A
Operating Temperature	T_{opr}	-20	-	100	



ORDERING INFORMATION


<u>J</u>	<u>OC</u>	<u>M</u>	<u>A</u>	<u>1</u>	<u>9</u>	<u>D</u>	<u>-SS4</u>	<u>/</u>
JieJie Microelectronics Co., Ltd.	Opto Coupler	MOS	A:1NO	1:V _{OFF} 20V	9:I _{ON} :2A	I _{FT} 1mA	SSON4	None:T1 R:T2

Packing Quantity	
Option	Quantity




Characteristics Curves


Max. Allowable LED Forward Current vs. Ambient Temperature




On-state Current vs. Ambient Temperature




LED Forward Current vs. LED Dropout Voltage




On-state Current vs. On-state Voltage



On Resistance vs. Ambient Temperature




Trigger LED Current vs. Ambient Temperature







T_{ON}, T_{OFF} vs. LED Forward Current



T_{ON}, T_{OFF} vs. Ambient Temperature




Off-state Current vs. Off-state Voltage



Off-state Current vs. Ambient Temperature




Package Dimension (Unit: mm)




Ref.	Dimensions					
	Millimeters			Inches		
	Min.	Typ.	Max.	Min.	Typ.	Max.
A	1.30		1.70	0.051		0.067
B	1.65		2.05	0.065		0.081
C	2.05		2.45	0.081		0.096
D	0.10		0.50	0.004		0.020
E	0.88		1.28	0.035		0.050
F	0.775		1.175	0.031		0.046
G	0.60		1.00	0.024		0.039
H	0.575		0.975	0.023		0.038

RECOMMENDED SOLDER MASK (Dimensions in mm unless otherwise stated)






CARRIER TAPE SPECIFICATIONS (Dimensions in mm unless otherwise stated)



Ref.	Dimensions					
	Millimeters			Inches		
	Min.	Typ.	Max.	Min.	Typ.	Max.
D0		1.50	1.60		0.059	0.063
P0	3.90	4.00	4.10	0.154	0.157	0.161
P1	3.90	4.00	4.10	0.154	0.157	0.161
P2	1.90	2.00	2.10	0.075	0.079	0.083
E	1.65	1.75	1.85	0.065	0.069	0.073
F	3.40	3.50	3.60	0.134	0.138	0.142
T	0.20	0.25	0.30	0.008	0.010	0.012
W	7.70	8.00	8.30	0.303	0.315	0.327



REFLOW INFORMATION



Temperature Min. (T _{smin})	100	150
Temperature Max. (T _{smax})	150	200
Time (t _s) from (T _{smin} to T _{smax})	60-120 seconds	60-120 seconds
Ramp-up Rate (t _L to t _P)	3 °C/second max.	3 °C/second max.
Liquidus Temperature (T _L)	183	217
Time (t _L) Maintained Above (T _L)	60-150 seconds	60-150 seconds
Peak Body Package Temperature	235 +0 /-5	260 +0 /-5
Time (t _P) within 5 °C of 260	10 seconds	10 seconds
Ramp-down Rate (T _P to T _L)	3-6 °C/second	3-6 °C/second
Time 25 °C to Peak Temperature	6 minutes max.	8 minutes max.



Note:

1. Reflow soldering is recommended at the temperatures and times shown, no more than three times.
2. Avoid direct contact between the epoxy body and any tools or surfaces exceeding its maximum storage temperature.
3. Application of pressure on the epoxy body is prohibited at elevated temperatures. In specific scenarios, any applied force must not exceed 2.5N.
4. Ensure the component has cooled to ambient temperature before proceeding with any subsequent manufacturing steps.
5. The component has a shelf life of one year when stored under standard conditions.
6. Recommend storage Temp.: 0~40°C;
Recommend storage humidity: <60%;
MSL level: MSL 3

Information furnished in this document is believed to be accurate and reliable. However, Jiangsu JieJie Microelectronics Co., Ltd. assumes no responsibility for the consequences of use without consideration for such information nor use beyond it. Information mentioned in this document is subject to change without notice, apart from that when an agreement is signed, Jiangsu JieJie complies with the agreement.

Products and information provided in this document have no infringement of patents. Jiangsu JieJie assumes no responsibility for any infringement of other rights of third parties which may result from the use of such products and information. This document supersedes and replaces all information previously supplied.



is a registered trademark of Jiangsu JieJie Microelectronics Co., Ltd.

Copyright © 2026 Jiangsu JieJie Microelectronics Co., Ltd. All rights reserved.